

5 ▶ 25A

To cut up to 6 mm**Internal air compressor****Single phase 230V (+/-15%)****Ideal for maintenance work, the CUTTER 25K is a plasma cutter with Inverter technology.****Internal air compressor**

With its internal compressor, the plasma 25K does not require an external supply of compressed air.

Quality cutting without distortion

The plasma 25K allows a high quality cutting even on painting surfaces:

- ✓ Cuts up to 6 mm steel, stainless steel and cast iron.
- ✓ Cuts up to 4 mm aluminium and copper.

Very accurate, the CUTTER 25K enables you to cut 0.6mm metal sheets at low intensity.



Ref. 030947

No HF Start

With the « Pilot Arc » system, the arc starts without having any contact with the welding sheet. Starting without HF avoids any electromagnetic interference (radio, computers, phones, medical equipment, etc...)

STEEL: 6 mm max ALU: 4 mm max
(Speed = 20 cm /min at 20A)**Easy to use, fast and safe**

- Torch: 4m with safety trigger to avoid accidental start.
- Internal compressor (noise): 60/70 Db.
- Reinforced protection for the use with generators and against permanent overvoltage up to 400V (factory tested).
- IP23 (protection against rain / dust), ideal for outside work.

Protected & compatible
Mini : 4 kW (5kVA)**Consumables**

Electrodes (x10)	Ref.040168	Diffusers (x2)	Ref.040175
Nozzles (x4)	Ref.040182	Tips (x10)	Ref.040151

AccessoriesCompass kit
Ref.040205For circular cut up to 134cm diameter.
Supplied with 3 axes: magnetic / to tip / to screwTorch trolley (on wheels)
Ref. 040199

For ease of use and to optimize the cutting distance as well as increase the nozzles durability.

CE EN 60974-1

50/60Hz	-AMP-	I ₂ A	mm		EN 60974-1(40°C)	AIR SYSTEM			cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)	
			Max cut	Clean cut		I _A (50%)	X _% I ₂ max	Pressure bar	L / mm	Kompressor inside	
230V 1~	16A	5-25	6	4	4	3	12	26	included	✓	22x45x31 /17,2
											4,1 kW 5,9 kVA